

CLASS	Nominal Size		Outside Diameter				Wall Thickness		Calculated Weight Plain Ends		
			Maximum		Minimum						
	mm	in	mm	in	mm	in	mm	in	kg/m	kg/ft	lb/ft
LIGHT (A)	90	3 1/2	102.0	3.98	101.1	3.95	3.2	0.126	7.761	2.366	5.22
EXTRA LIGHT (AA)	15	1/2	21.4	0.84	21.0	0.83	1.6	0.063	0.773	0.236	0.520
	20	3/4	26.9	1.06	26.4	1.04	1.6	0.063	0.990	0.302	0.666
	25	1	33.8	1.33	33.2	1.31	1.9	0.075	1.48	0.451	0.994
	32	1 1/4	42.5	1.67	41.9	1.65	1.9	0.075	1.89	0.576	1.27
	40	1 1/2	48.4	1.90	47.8	1.88	1.9	0.075	2.16	0.658	1.45
	50	2	60.2	2.30	59.6	2.35	1.9	0.075	2.72	0.829	1.83
	65	2 1/2	76.0	2.99	75.2	2.96	1.9	0.075	3.45	1.05	2.31
	80	3	88.7	3.49	87.9	3.46	2.1	0.083	4.46	1.36	3.00
	90	3 1/2	102.0	3.98	101.1	3.95	2.1	0.083	5.15	1.57	3.46
	100	4	113.9	4.48	113.0	4.45	2.3	0.091	6.31	1.92	4.23
	125	5	140.6	5.53	138.7	5.46	4.0	0.157	13.4	4.08	8.99
(AAA)	150	6	166.1	6.54	164.1	6.46	4.0	0.157	15.9	4.85	10.7
	25	1	33.8	1.33	33.2	1.31	1.6	0.063	1.259	0.384	0.847
	32	1 1/4	42.5	1.67	41.9	1.65	1.6	0.063	1.602	0.488	1.076
	40	1 1/2	48.4	1.90	47.8	1.88	1.6	0.063	1.835	0.559	1.233
	50	2	60.2	2.30	59.6	2.35	1.6	0.063	2.300	0.701	1.546
	65	2 1/2	76.0	2.99	75.2	2.96	1.6	0.063	2.920	0.890	1.962
	80	3	88.7	3.49	87.9	3.46	1.6	0.063	3.421	1.043	2.300
	100	4	113.9	4.48	113.0	4.45	1.9	0.075	5.226	1.593	3.513
	125	5	140.6	5.53	138.7	5.46	3.0	0.118	10.11	3.082	6.796
	150	6	166.1	6.54	164.1	6.46	3.0	0.118	11.99	3.655	8.059

Thickness Tolerances: ± 10%