

**BS EN 10025 S275 JR  
ASTM A 36**

**JIS G 3101 - SS400**

Thickness	Width x Length								
	1219mm x 2438mm 4' x 8'			1524mm x 3048mm 5' x 10'			1829mm x 6096mm 6' x 20'		
	Theoretical Weight								
mm	kg/pc	lb/pc	pcs/mt	kg/pc	lb/pc	pcs/mt	kg/pc	lb/pc	pcs/mt
3.0	75.069	165.497	13.3	117.336	258.679	8.5	281.623	620.866	3.6
4.5	110.063	242.645	9.1	172.033	379.264	5.8	412.909	910.299	2.4
6.0	145.058	319.795	6.9	226.730	499.849	4.4	544.195	1199.732	1.8
7.5	180.052	396.943	5.6	281.426	620.432	3.6	675.482	1489.168	1.5
8.0	191.717	422.659	5.2	299.659	660.628	3.3	719.244	1585.646	1.4
9.0	215.046	474.090	4.7	336.123	741.017	3.0	806.768	1778.601	1.2
10.0	238.376	525.524	4.2	372.587	821.405	2.7	894.292	1971.556	1.1
11.0	261.705	576.955	3.8	409.052	901.796	2.4	981.817	2164.514	1.0
12.0	285.035	628.388	3.5	445.516	982.185	2.2	1069.341	2357.469	0.9
13.0	308.365	679.821	3.2	481.981	1062.575	2.1	1156.876	2550.450	0.9
14.0	331.694	731.253	3.0	518.445	1142.965	1.9	1244.401	2743.406	0.8
15.0	355.024	782.686	2.8	554.910	1223.354	1.8	1331.925	2936.362	0.8
16.0	378.353	834.118	2.6	591.374	1303.744	1.7	1419.449	3129.318	0.7